



 **Made in  
GERMANY**

# POWERDISK

LARGE AREA LIGHTING

# POWERDISK

## Mobile large area light




### URNS NIGHT INTO DAY – A MOBILE MASTERPIECE

It's the perfect choice whenever you need even and powerful lighting quickly: the POWERDISK made by SONLUX. Equipped with the very latest LED technology including passive cooling, this wide area luminaire is a mobile masterpiece; because it combines maximum light output and mobility with superbly simple handling and outstanding robustness. The POWERDISK provides a remarkable 57,000 lumen of actually available luminous flux to powerfully and safely illuminate building and assembly sites or sports and leisure events, or to aid rescue and emergency operations.

### ADDITIONAL ADVANTAGES

- ⊕ Quick one-man installation
- ⊕ Maintenance-free (passive cooling)
- ⊕ Suitable for wind loads up to 150 km/h
- ⊕ Robust, impact-resistant construction
- ⊕ Anti-glare illumination thanks to opal cover
- ⊕ Dimmable
- ⊕ Environmentally friendly and conserves resources thanks to replaceable components





## POSSIBLE APPLICATIONS

- + Building trade
- + Industry
- + Emergency and rescue services  
(technical relief services, police, fire service,  
Red Cross, etc.)
- + Event management

# POWERDISK

## Features



Luminaire tested for use with limited surface temperature according to DIN EN 60598-2-24




High degree of protection IP 65



Impact-resistant and break-proof housing


Glare-reduced light thanks to opal cover lens made of impact-resistant and non-yellowing polycarbonate




Quick one-person installation




**DUSTPROOF**

 as per  
DIN EN 60598-1  
DIN EN 60529




**VIBRATION STABILITY**

 as per  
DIN EN 60598-1

### How passive cooling works

In our passively cooled lighting fixtures, the heat inside the fixture is dissipated via an aluminium element, thus obviating the need for active cooling and rendering the lighting fixtures maintenance free.




Environmentally friendly and conserves resources thanks to replaceable components

Versions with Casambi Bluetooth® control for wireless networking available




Integrated handle

Different connector systems and longer power supply cable on request




Dimmable version with push button switchable (1 / 0, 1 ... 100%)





Housing aluminum / stainless steel, cover plastic (polycarbonate, opal), 10 m power supply cable with mains plug, incl. adapter for spigot 30 mm (DIN 14640).



L 750, B 630, H 250 mm

$\Phi_V$  ..... 57.000 lm effective

..... 5.000 K\*,  $R_a \geq 80$   
..... 24 x COB-LED

..... 10 m, H07BQ-F  
..... yellow


..... IK10

\*3.000 K / 4.000 K - on request




230 V, 50-60 Hz


80P01000-0006	380 W	1 ... 100%	I	IP 65	E+F	15,7 kg
80P02000-0006	380 W	-	I	IP 65	E+F	14,8 kg
80P01001-0006	380 W	1 ... 100%	I	IP 65	E+F <sup>68</sup>	15,7 kg
80P02001-0006	380 W	-	I	IP 65	E+F <sup>68</sup>	14,8 kg
80P01006-0006	380 W	1 ... 100%	I	IP 65	CEE 6h	15,7 kg
80P02006-0006	380 W	-	I	IP 65	CEE 6h	14,8 kg
80P010CH-0006	380 W	1 ... 100%	I	IP 65	J	15,7 kg
80P020CH-0006	380 W	-	I	IP 65	J	14,8 kg



80P01000-0006	h (m)	Ø (m)	E (lx)
	3	9,40	2017
	5	15,67	726
	10	31,34	182
	20	62,68	45
	30	94,02	20



Housing aluminum / stainless steel, cover plastic (polycarbonate, opal), 10 m power supply cable with mains plug, incl. adapter for spigot 30 mm DIN 14640).



L 750, B 630, H 250 mm



230 V, 50-60 Hz



80P01000-0006.B	380 W	1 ... 100%	I	IP 65	E+F	15,6 kg
80P01001-0006.B	380 W	1 ... 100%	I	IP 65	E+F <sup>68</sup>	15,6 kg
80P01006-0006.B	380 W	1 ... 100%	I	IP 65	CEE 6h	15,6 kg
80P010CH-0006.B	380 W	1 ... 100%	I	IP 65	J	15,6 kg

$\Phi_v$  ..... 57.000 lm effective

..... 5.000 K\*, Ra ≥ 80  
..... 24 x COB-LED

..... 10 m, H07BQ-F  
..... yellow

..... IK10




\*3.000 K / 4.000 K - on request

## Smart Control

Smart Control stands for the intelligent remote control of our luminaires via mobile app from a mobile phone or tablet. It doesn't matter whether individual luminaires or groups of luminaires are to be controlled. All luminaires - even existing ones - can be controlled together with an integrated „Casambi“ module. Thus also our POWERTUBE II, POWERDISK and POWERCASE L. The luminaires are networked via Bluetooth from the mobile device to the luminaire and from luminaire to luminaire, which considerably increases the range of the luminaire network.


- ON/OFF
- Dimming
- Timer
- Scenes
- Animations











**Crank tripod "Premium"**

Steel, chrome plated, suitable for 16 & 28 mm spigots, safety bolt, load capacity 30 kg, self braking clutch/winch, fold-away crank, one adjustable stand to compensate uneven terrain

**incl. tripod adapter** 28 mm/30 mm (DIN 14640)

Packed dimensions:  
L 1.850, B 230, H 160 mm

95-0060-0014.D H max 3800, H min 1740, D 1300 mm 22,5 kg



**Crank tripod „LightmaXX“**

Galvanised steel, chrome-plated and powder-coated, with spigot adapter, automatic safety lock, load capacity 85 kg, 1 foot adjustable for levelling on uneven ground, self-braking coupling, fold-away elevator

**incl. tripod adapter** 28 mm/30 mm (DIN 14640)

**incl. clamping kit for tripod**

Pack dimensions:  
L 1.810, B 300, H 250 mm

95-0294-0014 H max 4130, H min 1750, D 1730 mm 25,0 kg



**Hinged feet with rubber pad**

For crank tripod "Premium", stainless steel, Set (3 pieces)




95-0266-0001 0,43 kg



**Bracing set**

3 x rope cord and peg

95-0267-0001 1,1 kg



**Tripod "Professionell"**

Stainless steel, air-cushioned for safe and comfortable operation, adjustable stand to compensate uneven terrain, load capacity 25 kg, with standard spigot 30 mm (DIN 14640), including bracing set (3 x rope cord and peg)




Packed dimensions:  
L 1.120, B 200, H 200 mm

95-0257-0014 H max 4450, H min 1100, D 1600 mm 13,3 kg

**Carrier box for Tripod "Premium"**

Wood, 2 carrier handles  
(set with tripod: right side)






 95-0265-0040	 L 1990, B 325, H 225 mm	 21,2 kg
---	---	---

**Carrier box for Tripod "Professionell"**

Wood, 3 carrier handles






 95-0258-0040	 L 1210, B 265, H 225 mm	 11,9 kg
---	---	---

**Carrier bag for Tripod "Professionell"**




Black, 2 carrier handles and shoulder belt



 95-0264-0001	 L 1150, B 130, H 240 mm	 0,6 kg
---	---	--

**Set Tripod "Professionell"**



The set includes:  
Tripod "Professionell", load capacity 25 kg,  
carrier box

 95-0257-0014S1	 L 1210, B 265, H 225 mm	 25,1 kg
---	---	---



**Set Crank tripod "Premium"**

The set includes:  
Crank tripod "Premium", load capacity 30 kg,  
tripod adapter, bracing set, carrier box

 95-0060-0014S1	L 1990, B 325, H 225 mm	 44,0 kg
---	-------------------------	---



Accessories



**Tripod adapter  
28 mm/30 mm (DIN 14640)**

Stainless steel, for connection to existing stands with 28 mm

---

 95-0254-0014	 L 108, D 38 mm	 0,5 kg
--	--	--




---



**Adapter for suspended mounting**

Ø 17 mm

---

 95-0255-0014	 L 70, B 65, H 72 mm	 0,12 kg
---	--	--




---



**Carrier bag  
for "POWERDISK"**

Handles, shoulder belt and transport rollers

---

 95-0259-0001	 L 850, B 240, H 680 mm	 6,6 kg
--	--	--




---



**Carrier box  
for "POWERDISK"**

Wood, 2 carrier handles






---

 95-0256-0040	 L 740, B 290, H 805 mm	 17 kg
--	--	---

---

**Set  
„POWERDISK“**






The set includes:  
“POWERDISK”,  
adapter for suspended mounting,  
carrier bag

	P				
230 V, 50-60 Hz					
80P01000-0006S2	380 W	✓	I	IP 65	E+F
80P02000-0006S2	380 W	-	I	IP 65	E+F
80P01001-0006S2	380 W	✓	I	IP 65	E+F <sup>68</sup>
80P02001-0006S2	380 W	-	I	IP 65	E+F <sup>68</sup>
80P01006-0006S2	380 W	✓	I	IP 65	CEE 6h
80P02006-0006S2	380 W	-	I	IP 65	CEE 6h
80P010CH-0006S2	380 W	✓	I	IP 65	J
80P020CH-0006S2	380 W	-	I	IP 65	J



**Set  
„POWERDISK“**

The set includes:  
“POWERDISK”,  
adapter for suspended mounting,  
carrier box

	P				
230 V, 50-60 Hz					
80P01000-0006S1	380 W	✓	I	IP 65	E+F
80P02000-0006S1	380 W	-	I	IP 65	E+F
80P01001-0006S1	380 W	✓	I	IP 65	E+F <sup>68</sup>
80P02001-0006S1	380 W	-	I	IP 65	E+F <sup>68</sup>
80P01006-0006S1	380 W	✓	I	IP 65	CEE 6h
80P02006-0006S1	380 W	-	I	IP 65	CEE 6h
80P010CH-0006S1	380 W	✓	I	IP 65	J
80P020CH-0006S1	380 W	-	I	IP 65	J



---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---



### Mobiles Licht für Profis – Made in Germany

Portable light for professionals – Made in Germany

*Éclairage mobile pour les professionnels –  
Fabriqué en Allemagne*

SONLUX Lighting GmbH

Frankenhäuser Straße 66  
99706 Sondershausen  
Germany

Phone +49 3632 6522 - 0  
Fax +49 3632 6522 - 822

www.sonlux.de  
info@sonlux.de



#### Tip with added value:

The digital version of this publication contains **interactive links** that lead you from the article number directly to the web.



Member of

**licht.de**